6” height

FS OR-G-SYG5

FS OR-G-SYG6

49” width

49” width

39.5” width

39.5” width

Cygnus
10’ x 10’ Truss System
Dye Sub Printed



TEMPLATE IS @ 1/2 SCALE
Panels SYG1 and SYG4:
Total Graphic Area: 43.5”w x 87.75”h
Finished Size: 39.5”w x 83.75”h

Panels SYG2 and SYG3:
Total Graphic Area: 53”w x 94”h
Finished Size: 49”w x 90”h

Panels SYG5 and SYG6:
Total Graphic Area: 51.25”w x 10”h
Finished Size: 47.25”w x 6”h

Template requires 1” bleed around the perimeter (2” around the perimeter when scaled to 200% and printed)

FS = Graphic is front side mounted (3/4” w velcro is applied to the back of the panel)
BS = Graphic is back side mounted (3/4”w velcro is applied to the front of the panel)
Notching = 7/8” square that is cut into the appropriate location.
Hinging= 3/4” strip of material that is created by notching the graphic. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

- CMYK Color Mode
- All Solid Coated Pantone colors should be called out in the art as spot colors
- Embed all images and support files
- Resolution must be 200-240 ppi @ 1/2 size, 100-120ppi @ 100% size
- All fonts must be created to outlines
- Do not scale artboard
- Background color/images must bleed to the edge of artboard
- Do not use spot colors from template in your artwork as they will not print

BS

OR-G-SYG1

BS

OR-G-SYG2

BS

OR-G-SYG3

BS

OR-G-SYG4

bleed area
trim line

gray area will be obstructed once finished and mounted

Cygnus
10′ x 10′ Truss System
Dye Sub Printed



TEMPLATE IS @ 1/2 SCALE
Panels SYG1 and SYG4:
Total Graphic Area: 43.5″w x 87.75″h
Finished Size: 39.5″w x 83.75″h

Panels SYG2 and SYG3:
Total Graphic Area: 53″w x 94″h
Finished Size: 49″w x 90″h

Panels SYG5 and SYG6:
Total Graphic Area: 51.25″w x 10″h
Finished Size: 47.25″w x 6″h

Template requires 1″ bleed around the perimeter (2″ around the perimeter when scaled to 200% and printed)

FS = Graphic is front side mounted (3/4″ w velcro is applied to the back of the panel)
BS = Graphic is back side mounted (3/4″w velcro is applied to the front of the panel)
Notching = 7/8″ square that is cut into the appropriate location.
Hinging= 3/4″ strip of material that is created by notching the graphic. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

– CMYK Color Mode
– All Solid Coated Pantone colors should be called out in the art as spot colors
– Embed all images and support files
– Resolution must be 200-240 ppi @ 1/2 size, 100-120ppi @ 100% size
– All fonts must be created to outlines
– Do not scale artboard
– Background color/images must bleed to the edge of artboard
– Do not use spot colors from template in your artwork as they will not print

BS

OR-G-SYG1

— bleed area
— trim line

BS

OR-G-SYG2

BS

OR-G-SYG3

BS

OR-G-SYG4

gray area will
be obstructed
once finished
and mounted

FSOR-G-SYG5

FS OR-G-SYG6